

## **Eurocalco CB+**

### **Description:**

First sheet of the form, coated on the front side to get very good printing results. On the back side coated with microcapsules that produce colour. It is used as an upper sheet or the form's original.

### **End uses:**

Business forms, Invoices

### **Print methods:**

Offset

### **Certificates:**

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [ISO 14001 Environment](#)
- [EMAS Leitza mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [Paper Profile Eurocalco](#)
- [Paper Profile Formula](#)

For applications that require specific certifications or approvals, please contact our sales teams.

## Eurocalco CB+

### Technical specifications

| Property          | Test Method      | Unit             | Tolerance   | 60   | 80   |
|-------------------|------------------|------------------|-------------|------|------|
| Substance         | ISO 536          | g/m <sup>2</sup> | ±4%         | 60   | 80   |
| Thickness         | ISO 534          | µm               | ± 4         | 75   | 98   |
| Relative humidity | TAPPI T502 om-89 | %                | ±5          | 40   | 40   |
| Curl              | TAPPI T427 um-85 | mm               | (4.0) - 0.0 | -2.0 | -2.0 |
| Whiteness D65/10° | ISO 11475        | ° CIE            | ±6          | 133  | 133  |
| Opacity           | ISO 2471         | %                | ± 4         | 81   | 87   |

### **GUARANTEES:**

20 years legibility of the copy under normal conditions of storage (T: 15-25 °C and 50-60% RH).

5 years shelf life under normal conditions of storage and with the original packaging.

Values are subject to change without notice.

Last update: 07/22/2026