

Eurocalco CB

Description:

Coated paper on the back side containing microcapsules that produce color. It is used as an upper sheet or the form's original.

Colors available: white, yellow, blue, pink, green.

End uses:

Business forms, Invoices

Print methods:

Offset

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [ISO 14001 Environment](#)
- [EMAS Leitzka mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [Paper Profile Eurocalco](#)
- [Paper Profile Formula](#)

For applications that require specific certifications or approvals, please contact our sales teams.

Eurocalco CB

Technical specifications

Property	Test Method	Unit	Tolerance	56	60	70	75	80	90	95
Substance	ISO 536	g/m ²	±4%	56	60	70	75	80	90	95
Thickness	ISO 534	µm	± 4	74	77	88	94	99	114	120
Opacity	ISO 2471	%	±4	81	82	87	90	89	91	93
Relative humidity	TAPPI T502 om-89	%	±5	43	43	43	40	40	40	40
Curl	TAPPI T427 um-85	mm	(4.0)-0.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Whiteness D65/10°	ISO 11475	°CIE	±6	138	138	138	138	138	138	138

GUARANTEES:

20 years legibility of the copy under normal conditions of storage (T: 15-25 °C and 50-60% RH).

5 years shelf life under normal conditions of storage and with the original packaging.

Values are subject to change without notice.

Last update: 04/15/2026