

Eurokote A

Description:

Cast-coated paper for self-adhesive labels.

End uses:

Label facestock, Wine and spirit labels

Print methods:

Offset, Serigraphy, Letterpress, Stamping, Rotogravure, Flexo

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [EMAS Leitza mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [Paper Profile Eurokote](#)

For applications that require specific certifications or approvals, please contact our sales teams.

Eurokote A

Technical specifications

Property	Test Method	Unit	Tolerance	80	83	90	130	170	180
Substance	ISO 536	g/m ² lbs	± 4 %	80	83	90	130	170	180
		lbs		54	56	61	88	115	67
		g/m ²							
Thickness	ISO 534	µm mils	80-90gr ± 4	78	81	88	131	180	190
		mils	130-180gr ± 5%	3	3.2	3.5	5.2	7.1	7.5
		µm							
Paper gloss 20	TAPPI T-653 pm-07	%	± 5	35	35	35	41	41	41
Brightness R457/D65	ISO 2470 / ISO 11475	%	± 2 / ± 5	90/106	90/106	90/106	90/106	90/106	90/106
Opacity	ISO 2471	%	± 3	89	89	92	97	99	99
Absolute humidity	ISO 287	%	± 1	4.7	4.7	4.7	5.0	5.0	5.0
Bekk smoothness (coated side)	ISO 5627	s	80-90gr ± ≥400 130-180gr ± ≥350	500	500	500	500	500	500
Cobb (uncoated side)	ISO 535	g/m ²	80-90gr ± 5 130-180gr ≤70	22	22	22	35	35	35

Values are subject to change without notice.

Last update: 06/16/2026