Eurokote A WS

Description:

Cast-coated paper for wet-strength self-adhesive labels.

End uses:

Label facestock, Wine and spirit labels

Print methods:

Offset, Rotogravure, Serigraphy, Stamping, Flexo

Certificates:

- PEFC Chain of Custody (multisite)
- FSC Chain of Custody (multisite)
- ISO 14001 Environment
- EMAS Leitza mill
- ISO 50001 Energy Efficiency
- ISO 9001 Quality
- ISO 45001 Health and Safety - Lecta
- Paper Profile Eurokote

For applications that require specific certifications or approvals, please contact our sales teams.

Eurokote A WS

Technical specifications

Property	Test Method	Unit	Tolerance	80	90
Substance	ISO 536	g/m²	± 4 %	80	90
Thickness	ISO 534	µm	± 4	74	86
Paper gloss 20	TAPPI T-653 pm-07	%	± 5	35	35
Brightness R457/D65	ISO 2470 / ISO 11475	%	± 2 / ± 5	89/103	89/103
Opacity	ISO 2471	%	-2	92	92
Absolute humidity	ISO 287	%	±1	5.0	5.0
Wet opacity	ISO 2471	%	-3	81	83
Bekk smoothness (coated side)	ISO 5627	s	≥ 800	2.000	2.000
Cobb (uncoated side)	ISO 535	g/m²	± 5	18	18
Wet tensile strength MD	ISO 3781	kN/m	≥ 1.0	1.0	1.0
Wet tensile strength CD	ISO 3781	kN/m	≥ 0.6	0.7	0.7

Values are subject to change without notice.
Last update: 07/22/2026