

## Metalvac A HG

### Description:

Metallized paper for self-adhesive labels with a high gloss finish.

### End uses:

Label facestock, Wine and spirit labels

### Print methods:

Conventional offset, UV offset, Rotogravure solvent-based, Flexo solvent-based, Flexo UV

### Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [EMAS Leitza mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [FSSC 22000 Food Safety - Leitza](#)
- [Paper Profile Metalvac](#)

For applications that require specific certifications or approvals, please contact our sales teams.

## Metalvac A HG

### Technical specifications

Property	Test Method	Unit	Tolerance	83
Substance	ISO 536	g/m <sup>2</sup>	± 4 %	83
Thickness	ISO 534	µm	± 5	67
Gloss (silver, plain)	ISO 7668	% <sub>o</sub>	± 10%	690
Cobb (uncoated side)	ISO 535	g/m <sup>2</sup>	± 5	23
Absolute humidity	ISO 287	%	± 1	3.5
Dry tensile strength MD	ISO 1924- 2	Kg/15mm	-1	7.5
Dry tensile strength CD	ISO 1924- 2	Kg/15mm	-0.5	4.4
Dry tear resistance MD/CD	ISO 1974	gf	-5.0	43/45

**Storage recommendations:** Ideally, paper should be stored at 50% (±5%) relative humidity and 23 °C (±2) and covered with original packaging. Avoid extreme temperature and humidity.

**Recommendations of use:** Best Before 12 months after dispatch from our factory.

Customers are responsible of their own product testing, evaluation and safety procedures.

Values are subject to change without notice.

Last update: 04/15/2026