Metalvac A HG WS

Description:

Metallized paper for self-adhesive labels. For end uses requiring resistance to moisture.

End uses:

Label facestock, Wine and spirit labels

Print methods:

Conventional offset, UV offset, Rotogravure solvent-based, Flexo solvent-based, Flexo UV

Certificates:

- PEFC Chain of Custody (multisite)
- FSC Chain of Custody (multisite)
- ISO 14001 Environment
- EMAS Leitza mill
- ISO 50001 Energy Efficiency
- ISO 9001 Quality
- ISO 45001 Health and Safety - Lecta
- FSSC 22000 Food Safety - Leitza
- Paper Profile Metalvac

For applications that require specific certifications or approvals, please contact our sales teams.

Metalvac A HG WS

Technical specifications

Property	Test Method	Unit	Tolerance	63	83
Substance	ISO 536	g/m²	± 4%	63	83
Thickness	ISO 534	µm	± 5	60	70
Gloss (silver, plain)	ISO 7668	‰	± 20%	500	610
Cobb (uncoated side)	ISO 535	g/m²	± 4	19	18
Absolute humidity	ISO 287	%	± 1	3.5	3.5
Dry tensile strength MD	ISO 1924-2	Kg/15mm	-1	6	7.5
Dry tensile strength CD	ISO 1924-2	Kg/15mm	-0.5	3.2	5
Wet tensile strength MD	ISO 3781	Kg/15mm	-0.5	1.8	1.9
Wet tensile strength CD	ISO 3781	Kg/15mm	-0.5	1.1	1.6
Alcali resistance	DIN 16524-7	s	≥10	≥15	≥15

Values are subject to change without notice.
Last update: 07/22/2026