Metalvac R

Description:

Metallized paper with a very high gloss finish. Recommended for wrapping paper, bags or decoration.

End uses:

Retail labels, bags and packaging

Print methods:

Offset, Rotogravure, Flexo

Certificates:

- PEFC Chain of Custody (multisite)
- FSC Chain of Custody (multisite)
- ISO 14001 Environment
- EMAS Leitza mill
- ISO 50001 Energy Efficiency
- ISO 9001 Quality
- ISO 45001 Health and Safety - Lecta
- FSSC 22000 Food Safety - Leitza
- Paper Profile Metalvac

For applications that require specific certifications or approvals, please contact our sales teams.

Metalvac R

Technical specifications

Property	Test Method	Unit	Tolerance	63	70	73
Substance	ISO 536	g/m²	± 4 %	63	70	73
Thickness	ISO 534	µm	± 5	56	60	63
Gloss (silver, plain)	ISO 7668	‰	± 20%	355	355	355
Cobb (uncoated side)	ISO 535	g/m²	± 4	17	18	18
Absolute humidity	ISO 287	%	± 1	4	4	4
Dry tensile strength MD	ISO 1924-2	Kg/15mm	≥4.5	6.0	6.5	6.5
Dry tensile strength CD	ISO 1924-2	Kg/15mm	≥2.5	3.2	4	4

Values are subject to change without notice.

Last update: 07/22/2026