

Metalvac E UV

Description:

Metallized label paper designed for non-returnable containers such as bottles, cans and jars. Specifically designed for UV curing inks

End uses:

Labels for 1-way bottles, Wraparound labels, Wine and spirit labels

Print methods:

UV offset, Flexo UV

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [ISO 14001 Environment](#)
- [EMAS Leitza mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [FSSC 22000 Food Safety - Leitza](#)
- [Paper Profile Metalvac](#)

For applications that require specific certifications or approvals, please contact our sales teams.

Metalvac E UV

Technical specifications

Property	Test Method	Unit	Tolerance	73	83	93
Substance	ISO 536	g/m ²	± 4 %	73	83	93
Thickness	ISO 534	µm	± 5	63	70	80
Gloss (silver, plain)	ISO 7668	‰	± 65	450	450	450
Cobb (uncoated side)	ISO 535	g/m ²	± 4	18	18	18
Absolute humidity	ISO 287	%	± 1	5.0	5.0	5.0
Relative humidity	TAPPI T502	%	± 7	47	47	47
Dry tensile strength MD	ISO 1924-2	kg/15mm	-1	6.2	7.0	7.5
Dry tensile strength CD	ISO 1924-2	kg/15mm	-0.5	4.3	5.0	5.5

Values are subject to change without notice.

Last update: 07/22/2026