Metalvac FP OH Proof

Description:

Metallized paper designed to deliver high visual impact while maintaining stable surface performance under alcohol exposure, suitable for use as a lamination layer.

End uses:

Flexible packaging, Food contact, Alcohol resistant packaging (perfumes, cosmetics, etc.), Liqueur-filled chocolate packaging (pouches, sachets, etc.), Wrapping solutions, Lamination

Print methods:

Conventional offset, Flexo solvent-based, Rotogravure solvent-based

Certificates:

- PEFC Chain of Custody (multisite)
- FSC Chain of Custody (multisite)
- REACH regulation Lecta
- ISO 14001 Environment
- EMAS Leitza mill
- ISO 50001 Energy Efficiency
- ISO 9001 Quality
- ISO 45001 Health and Safety - Lecta
- FSSC 22000 Food Safety - Leitza
- Paper Profile Metalvac

For further details regarding compliance with food contact regulation, please contact our sales teams.

Metalvac FP OH Proof

Technical specifications

Property	Test Method	Unit	Tolerance	53
Substance	ISO 536	g/m²	±4%	53
Thickness	ISO 534	µm	±5	48
Gloss (silver, plain)	ISO 7668	‰	±20%	420
Cobb (uncoated side)	ISO 535	g/m²	±4	22
Absolute humidity	ISO 287	%	±1	4.5
Relative humidity	TAPPI T502	%	±7	40
Dry tensile strength MD	ISO 1924-2	kg/15mm	-1	4.8
Dry tensile strength CD	ISO 1924-2	kg/15mm	-0.5	2.7

Values are subject to change without notice.
Last update: 04/15/2026