

Creaset A Gloss

Description:

Supercalendered one-side coated paper for self-adhesive labels with a high-gloss finish, featuring high surface smoothness.

End uses:

Self-adhesive label facestock

Print methods:

Conventional offset, UV offset, Flexo solvent-based, Flexo water-based, Flexo UV, Rotogravure solvent-based, Rotogravure water-based, Inkjet UV, Inkjet water-based

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [EMAS Motril mill](#)
- [ISO 50001 Energy Efficiency](#)
- [Paper Profile Creaset - Motril](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [FSSC 22000 Food Safety - Motril](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

Creaset A Gloss

Technical specifications

Property	Test Method	Unit	Tolerance	80	90
Substance	ISO 536	g/m ²	±4%	80	90
	TAPPI T410				
Thickness	ISO 534	µm	±4%	65.5	74
	TAPPI T411				
Paper gloss	ISO 8254-1	%	±5	72	72
	TAPPI T480				
Parker roughness	ISO 8791-4	µm	+0.2	0.9	0.9
	TAPPI T555				
Cobb (uncoated side)	ISO 535	g/m ²	±4	24	24
	TAPPI T441				
Tensile strength MD	ISO 1924-2	kN/m	-0.7	4.4	4.6
	TAPPI T494				
Tensile strength CD	ISO 1924-2	kN/m	-0.3	2.5	2.7
	TAPPI T494				

Values are subject to change without notice.

Last update: 04/15/2026