

Creaset A HWS

Description:

One-side coated paper for wet-strength self-adhesive labels.

End uses:

Self-adhesive label facestock

Print methods:

Conventional offset, UV offset, Flexo solvent-based, Flexo water-based, Flexo UV, Inkjet UV, Inkjet water-based

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [EMAS Motril mill](#)
- [ISO 50001 Energy Efficiency](#)
- [Paper Profile Creaset - Motril](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [FSSC 22000 Food Safety - Motril](#)

For applications that require specific certifications or approvals, please contact our sales teams.

Creaset A HWS

Technical specifications

Property	Test Method	Unit	Tolerance	70	80
Substance	ISO 536	g/m ²	±4%	70	80
	TAPPI T410				
Thickness	ISO 534	µm	±4%	59	67
	TAPPI T411				
Paper gloss	ISO 8254-1	%	±5	68	68
	TAPPI T480				
Parker roughness	ISO 8791-4	µm	<1.4	1.1	1.1
	TAPPI T555				
Cobb (uncoated side)	ISO 535	g/m ²	±3	12	12
	TAPPI T441				
Dry tensile strength MD	ISO 1924-2	kN/m	-0.5	3.6	4.3
	TAPPI T494				
Dry tensile strength CD	ISO 1924-2	kN/m	-0.5	2.8	3.3
	TAPPI T494				
Wet tensile strength MD	ISO 3781	kN/m	-0.2	1.0	1.1
	TAPPI T456				
Wet tensile strength CD	ISO 3781	kN/m	-0.2	0.9	1.0
	TAPPI T456				
Alcali resistance	DIN 16524-7	min	ref.	>60	>60

Values are subject to change without notice.

Last update: 04/15/2026