

Creaset FP

Description:

One-side coated paper for flexible packaging applications. Suitable for laminating or extruding with other packaging materials. Without OBA added

End uses:

Flexible packaging

Print methods:

Flexo, Offset, Rotogravure

Certificates:

- [Creaset Range List of certificates](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [EMAS Motril mill](#)
- [ISO 50001 Energy Efficiency](#)
- [Paper Profile Creaset - Motril](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [FSSC 22000 Food Safety - Motril](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

Creaset FP

Technical specifications

Property	Test Method	Unit	Tolerance	60	70	80
Substance	ISO 536	g/m ²	±4%	60	70	80
	TAPPI T410			60	70	80
Thickness	ISO 534	µm	±4%	51	57	65
	TAPPI T411			51	57	65
Taber stiffness MD	ISO 2493	gf*cm	-25%	0.4	0.55	0.75
	TAPPI T489			0.4	0.55	0.75
Cobb (uncoated side)	ISO 535	g/m ²	±5	23	23	23
	TAPPI T411			23	23	23
Opacity	ISO 2471	%	-2	79	83	87
	TAPPI T519			79	83	87

Values are subject to change without notice.

Last update: 04/15/2026