

## Creaset RG

### Description:

One-side coated gloss paper for hot melt wraparounds such as yoghurt banderoles. For rotogravure printing.

### End uses:

Wraparound labels, Flexible packaging

### Print methods:

Rotogravure

### Certificates:

- [Creaset Range List of certificates](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [EMAS Motril mill](#)
- [ISO 50001 Energy Efficiency](#)
- [Paper Profile Creaset - Motril](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [FSSC 22000 Food Safety - Motril](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

## Creaset RG

### Technical specifications

Property	Test Method	Unit	Tolerance	90	95	110
Substance	ISO 536 TAPPI T410	g/m <sup>2</sup>	±4%	90	95	110
Taber stiffness CD	ISO 2493	gf*cm	-10%	0.75	0.9	1.2
Taber stiffness MD	ISO 2493	gf*cm	-10%	1.6	1.9	2.4
Tensile strength CD	ISO 1924-2	kN/m	-0.4	2.9	-	3.5
Tensile strength MD	ISO 1924-2	kN/m	-0.7	5.3	5.5	6
Thickness	ISO 534 TAPPI T411	µm	±4%	79	84	98
Bekk smoothness (coated side)	ISO 5627 TAPPI T475	sec.	≥0,8*STD	1000	900	600
Cobb (uncoated side)	ISO 535 TAPPI T441	g/m <sup>2</sup>	±5	25	25	25
Paper gloss	ISO 8254 TAPPI T480	%	±5	75	75	75

Values are subject to change without notice.

Last update: 04/15/2026