

Creaset Suit

Description:

One-side coated gloss paper for standard or wraparound labels

End uses:

Labels for 1-way bottles, Wraparound labels

Print methods:

Conventional offset, UV offset, Flexo solvent-based, Flexo water-based, Flexo UV, Rotogravure solvent-based, Rotogravure water-based, Inkjet UV, Inkjet water-based

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [EMAS Motril mill](#)
- [ISO 50001 Energy Efficiency](#)
- [Paper Profile Creaset - Motril](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [FSSC 22000 Food Safety - Motril](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

Creaset Suit

Technical specifications

Property	Test Method	Unit	Tolerance	80	90	100	120
Substance	ISO 536 TAPPI T410	g/m ²	±4%	80	90	100	120
Thickness	ISO 534 TAPPI T411	µm	±4%	69	78	90	109
Paper gloss	ISO 8254-1 TAPPI T480	%	±5	66	66	67	68
Bekk smoothness (coated side)	ISO 5627 TAPPI T475	s	-150	1100	850	600	420
Cobb (uncoated side)	ISO 535 TAPPI T441	g/m ²	±5	23	23	23	24
Absolute humidity	ISO 638	%	±0.5	4.5	4.5	4.5	3.9
Relative humidity	TAPPI T502	%	±5	45	45	45	45
Tensile strength MD	ISO 1924-2 TAPPI T494	kN/m	-0.3	4.8	5.1	5.4	6.5
Tensile strength CD	ISO 1924-2 TAPPI T494	kN/m	-0.3	3	3.2	3.4	4.1

Values are subject to change without notice.

Last update: 04/15/2026