Creaset A Gloss

Description:

Supercalendered one-side coated paper for self-adhesive labels with a high-gloss finish, featuring high surface smoothness.

End uses:

Self-adhesive label facestock

Print methods:

Conventional offset, UV offset, Flexo solvent-based, Flexo water-based, Flexo UV, Rotogravure solvent-based, Rotogravure water-based, Inkjet UV, Inkjet water-based

Certificates:

- PEFC Chain of Custody (multisite)
- FSC Chain of Custody (multisite)
- ISO 14001 Environment
- EMAS Motril mill
- ISO 50001 Energy Efficiency
- Paper Profile Creaset - Motril
- ISO 9001 Quality
- ISO 45001 Health and Safety - Lecta
- FSSC 22000 Food Safety - Motril

For further details regarding compliance with food contact regulation, please contact our sales teams.

Creaset A Gloss

Technical specifications

Property	Test Method	Unit	Tolerance	80	90
Substance	ISO 536 TAPPI T410	g/m²	±4%	80	90
Thickness	ISO 534 TAPPI T411	µm	±4%	65.5	74
Paper gloss	ISO 8254-1 TAPPI T480	%	±5	72	72
Parker roughness	ISO 8791-4 TAPPI T555	µm	+0.2	0.9	0.9
Cobb (uncoated side)	ISO 535 TAPPI T441	g/m²	±4	24	24
Tensile strength MD	ISO 1924-2 TAPPI T494	kN/m	-0.7	4.4	4.6
Tensile strength CD	ISO 1924-2 TAPPI T494	kN/m	-0.3	2.5	2.7

Values are subject to change without notice.

Last update: 07/22/2026