Creaset Bag

Description:

One-side coated gloss paper for shopping bags

End uses:

Retail labels, bags and packaging, Flexible packaging

Print methods:

Flexo, Offset

Certificates:

- Creaset Range List of certificates
- PEFC Chain of Custody (multisite)
- FSC Chain of Custody (multisite)
- ISO 14001 Environment
- EMAS Motril mill
- ISO 50001 Energy Efficiency
- Paper Profile Creaset - Motril
- ISO 9001 Quality
- ISO 45001 Health and Safety - Lecta
- FSSC 22000 Food Safety - Motril

For further details regarding compliance with food contact regulation, please contact our sales teams.

Creaset Bag

Technical specifications

Property	Test Method	Unit	Tolerance	90	100	110	120
Substance	ISO 536 TAPPI T410	g/m²	±4%	90	100	110	120
Thickness	ISO 534 TAPPI T411	µm	±4%	82	91	100	108
Parker roughness	ISO 8791-4 TAPPI T555	µm	+0,3	1.3	1.3	1.3	1.0
Cobb (uncoated side)	ISO 535 TAPPI T441	g/m²	±4	25	25	25	25
Tensile strength MD	ISO 1924-2 TAPPI T494	kN/m	>0.9*Std	5.7	6.2	6.9	7.7
Tensile strength CD	ISO 1924-2 TAPPI T494	kN/m	>0.9*Std	3.5	3.7	3.9	4.3
Bursting strength	ISO 2758 TAPPI T403	kg/cm²	-0.5	2.6	2.8	3.0	3.2

**Service conditions must be consulted with the Commercial department for 100 gsm and 110 gsm.*

Values are subject to change without notice.

Last update: 07/22/2026