# Diva Art Duo Digital

## Description:

Diva Art Duo has been specially designed for creative uses of graphic and luxury packaging.

- Solid Bleached Sulphate (SBS) paperboard, certified FSC® C011032, PEFC available from production
- Two-side coated paperboard with a silk finish
- Excellent printability and brilliant color reproduction
- Exceptional cracking resistance
- Perfect folding characteristics
- Outstanding finishing and converting properties
- Good caliper and stiffness
- Consistent smoothness and whiteness

## End uses:

Books, Brochures, Covers, Direct mail, Folders, Folding materials, Inserts, Magazines, Packaging, Postcards, Tags

## Print methods:

HP Indigo, Digital, Flexo, Offset

## Certificates:

- HP Indigo - Digital Diva Art Duo 250gsm
- HP Indigo - Digital Diva Art Duo 280gsm
- HP Indigo - Digital Diva Art Duo 300gsm
- HP Indigo - Digital Diva Art Duo 330gsm
- HP Indigo - Digital Diva Art Duo 350gsm
- HP Indigo - Digital Diva Art Duo 380gsm
- PEFC Chain of Custody (multisite)
- FSC Chain of Custody (multisite)
- REACH regulation Lecta
- ISO 14001 Environment
- ISO 50001 Energy Efficiency
- ISO 9001 Quality
- Paper Profile Diva Art Duo Digital
- ISO 45001 Health and Safety - Lecta

For further details regarding compliance with food contact regulation, please contact our sales teams.

# Diva Art Duo Digital

## Technical specifications

| Property | Test Method | Unit | Tolerance | 250 | 280 | 300 | 330 | 350 | 380 |
|---|---|---|---|---|---|---|---|---|---|
| Substance | ISO 536<br>TAPPI T410 | g/m² | ±5% | 250 | 280 | 300 | 330 | 350 | 380 |
| Thickness | ISO 534<br>TAPPI T411 | µm | ±5% | 272 | 311 | 338 | 378 | 405 | 440 |
| Brightness<br>R457/D65 | ISO 2470-2<br>TAPPI T452 | % | ±2 | 102 | 102 | 102 | 102 | 102 | 102 |
| Whiteness<br>D65/10° | ISO 11475<br>TAPPI T562 | CIE | ±3 | 132 | 132 | 132 | 132 | 132 | 132 |
| Paper gloss | ISO 8254-1<br>TAPPI T480 | % | ±5 | 30 | 30 | 30 | 30 | 30 | 30 |
| Taber stiffness<br>MD | ISO 2493<br>TAPPI T556 | mN | -25% | 114 | 132 | 203 | 284 | 345 | 406 |
| Taber stiffness<br>CD | ISO 2493<br>TAPPI T556 | mN<br>-25% | - | 71 | 77 | 122 | 162 | 183 | 213 |
| Parker roughness | ISO 8791-4<br>TAPPI T555 | µm | ≤2.5 | 2 | 2 | 2 | 2 | 2 | 2 |
| Relative humidity | TAPPI T502 | % | ±7 | 48 | 48 | 48 | 48 | 48 | 48 |

# Diva Art Duo Digital

**Storage recommendations**

Paper dimensions are very sensible to humidity variations that is why we supply paper in waterproof packaging. Once the packaging is opened, a moisture exchange can take place between the paper and the environment.

Ideally, the paper should be stocked in pressrooms conditioned to 48% (±7) relative humidity and 23ºC (±2) temperature. In any case, extremes of temperature and humidity must be avoided.

The technical properties of the product are guaranteed for 12 months after the production date.

Before starting a production run, check that the printability is correct on both sides of 30-50 sheets.

Values are subject to change without notice.

Last update: 04/15/2026