Diva Art Metal

Description:

Diva Art Metal is a high-vacuum metallized paperboard on one side, specially designed for creative uses of graphic and luxury packaging. Diva Art Metal gives excellent printing and converting results.

End uses:

Folders, Folding materials, Packaging, Postcards, Inserts

Print methods:

UV offset, Flexo UV

Certificates:

- PEFC Chain of Custody (multisite)
- FSC Chain of Custody (multisite)
- REACH regulation Lecta
- ISO 14001 Environment
- ISO 50001 Energy Efficiency
- ISO 9001 Quality
- ISO 45001 Health and Safety - Lecta

For applications that require specific certifications or approvals, please contact our sales teams.

Diva Art Metal

Technical specifications

Property	Test Method	Unit	Tolerance	250	300	350
Substance	ISO 536	g/m²	±5%	250	300	350
Thickness	ISO 534	µm	±5%	300	360	420
Bulk	ISO 534	cm3/g	-	1.2	1.2	1.2
Paper gloss	ISO 7668	%	±20%	185	185	185
Taber stiffness MD	ISO 2493	gf*cm	±30%	65	120	195
Taber stiffness CD	ISO 2493	gf*cm	±30%	35	60	95
Absolute humidity	ISO 287	%	±1%	3.0	3.0	3.0
Relative humidity	TAPPI T502 om-89	%	±7%	30	30	30

Diva Art Metal

Values are subject to change without notice.
Last update: 04/15/2026