

Linerset CCK Duo

Description:

Two-side clay-coated release paper for siliconization with special reverse side. Good dimensional stability and extra lay-flatness. Generally used for graphic films applications.

End uses:

Industrial uses, RBP and film carriers

Certificates:

- [Linerset CCK Duo - List of Certificates](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [ISO 14001 Environment](#)
- [EMAS Motril mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [Paper Profile Linerset CCK](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

Linerset CCK Duo

Technical specifications

Property	Test Method	Unit	Tolerance	120	128	135
Substance	ISO 536 TAPPI T410	g/m ²	±4%	120	128	135
Thickness	ISO 534 TAPPI T411	µm	±4%	114	121	128
Parker roughness (top side)	ISO 8791-4 TAPPI T555	µm	≤2.5	2	2	2
Parker roughness (back side)	ISO 8791-4 TAPPI T555	µm	≤4.0	2.9	2.9	2.9
Tensile strength MD	ISO 1924-2 TAPPI T 494	kN/m	-0.7	6.5	7	7.5
Tensile strength CD	ISO 1924-2 TAPPI T 494	kN/m	-0.3	3.5	3.8	4.1
Cobb-Unger (top side)	SCAN-P 37:77	g/m ²	≤0.8	0.4	0.4	0.4
Cobb-Unger (back side)	SCAN-P 37:77	g/m ²	≤2.0	1.2	1.2	1.2

Values are subject to change without notice.
Last update: 07/22/2026