

Linerset CCK

Description:

One-side clay-coated release paper for siliconization. Good dimensional stability and lay-flatness. Low grammages generally used for labelling and high grammages for graphic films applications.

End uses:

Labels, Industrial uses, RBP and film carriers

Certificates:

- [Linerset CCK - List of Certificates](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [ISO 14001 Environment](#)
- [EMAS Motril mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)
- [Paper Profile Linerset CCK](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

Linerset CCK

Technical specifications

Property	Test Method	Unit	Tolerance	55	61	74	80	86	100	120	128	135
Substance	ISO 536 TAPPI T410	g/m ²	±4%	55	61	74	80	86	100	120	128	135
Thickness	ISO 534 TAPPI T411	µm	±4%	55	61	74	80	86	101	118	124	131
Parker roughness	ISO 8791-4 TAPPI T555	µm	≤2.5	2.2	2.2	2.2	2.2	2.2	2.2	2	2	2
Tensile strength MD	ISO 1924-2 TAPPI T 494	kN/m	-0.7	4	4.1	4.4	4.6	4.9	5.3	6.5	7	7.5
Tensile strength CD	ISO 1924-2 TAPPI T 494	kN/m	-0.3	2.0	2.1	2.5	2.6	2.6	2.7	3.5	3.8	4.1
Cobb-Unger	SCAN-P 37:77	g/m ²	≤0.8	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4

Values are subject to change without notice.
Last update: 07/22/2026