

Coral Vellum

Description:

Uncoated, calendered woodfree paper for self-adhesive labels.

End uses:

Self-adhesive label facestock

Print methods:

Flexo, Thermal transfer, Offset, Laser/Dry toner

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [ISO 14001 Environment](#)
- [EMAS Zaragoza mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

Coral Vellum

Technical specifications

Property	Test Method	Unit	Tolerance	60	65	68
Substance	ISO 536 TAPPI T410	g/m ²	±4%	60	65	68
Thickness	ISO 534 TAPPI T411	µm	±2	59	63	65
Brightness R457/D65	ISO 2470-2	%	±2	104	104	104
Opacity	ISO 2471 TAPPI T519	%	-2	86	87	88
Bekk smoothness	TAPPI T479 DIN 5627	s	≥0.9*STD	200	220	250
Tensile strength MD	ISO 1924-2 TAPPI T494	kN/m	-1	4.8	4.9	5
Tensile strength CD	ISO 1924-2 TAPPI T494	kN/m	-0.5	2.3	2.4	2.5

Values are subject to change without notice.

Last update: 07/09/2026