CreatorUrban Backlight DPI

Description:

One-side coated paper for backlight advertising panels such as bus shelters

End uses:

Advertising :: indoor, Advertising :: outdoor

Print methods:

Inkjet ecosolvent, Inkjet mild solvent, Inkjet solvent, Inkjet UV, Inkjet latex

Certificates:

- PEFC Chain of Custody (multisite)
- FSC Chain of Custody (multisite)
- ISO 14001 Environment
- EMAS Sant Joan
- ISO 50001 Energy Efficiency
- ISO 9001 Quality
- Paper Profile CreatorUrban
- ISO 45001 Health and Safety - Lecta

For applications that require specific certifications or approvals, please contact our sales teams.

CreatorUrban Backlight DPI

Technical specifications

Property	Test Method	Unit	Tolerance	135	150	170	200
Substance	ISO 536 TAPPI T410	g/m²	±4%	135	150	170	200
Thickness	ISO 534 TAPPI T411	µm	±4%	137	155	178	215
Parker roughness	ISO 8791-4 TAPPI T555	µm	±1,3*STD	1,5	1,5	1,5	1,5
Cobb (uncoated side)	ISO 535	g/m²	±45	36	37	39	40

Values are subject to change without notice.
Last update: 07/22/2026